

IPC-3026

6-Slot Desktop/ Wallmount Chassis for Half-Size SBC

NEW



Features


- Stylish and compact design for embedded applications
- LED indicators and alarm notification for system fault detection, including Power, HDD, Temp, Fan
- Shock-resistant disk drive bay to hold one 3.5" disk drives (or two 2.5" disk drive with front access using special bracket)
- Supports PICMG1.3/ PICMG1.0 6-slot half-size passive backplane.
- Adopts 150W power supply




Specifications

Disk Drive Bay	3.5"	Front-accessible	Internal
		-	1
Cooling	Fan	1 (9 cm 53 CFM)	
	Air Filters	Yes	
I/O Interface	USB	2 (Front accessible), 2 (Rear accessible)	
Miscellaneous	LED Indicators	Power, HDD, Temp, Fan	
	Front Panel	Reset button, Power switch	
	Rear Panel	Reserved 9-pin D-SUB opening, 25-pin Opening, DVI opening, USB ports	
Environment	Temperature	Operating: 0 ~ 40° C (32 ~ 104° F)	Non-operating: -20 ~ 60° C (-4 ~ 140° F)
	Humidity	10 ~ 85% @ 40° C, non-condensing	10 ~ 95% @ 40° C, non-condensing
	Vibration (5-500 Hz)	1 Grms	2 G
	Shock	10 G (with 11 ms duration, half sine wave)	30 G
Physical Characteristics	Dimensions (W x H x D)	150 x 222 x 270 mm	


Front View



Rear View




Other View



Dimensions

Unit: mm [inch]



Ordering Information

Model name	Power Supply
IPC-3026BP-00XE	Without power supply
IPC-3026BP-15ZE	1757003464

Power Supply Options

Part number	Specifications	
	Watt	Input
1757003464 (ATX, PFC)	150W	AC 100 ~ 120 V/AC200 ~ 240V

Backplane Options

Model	PICMG1.3/1.0	PCIe	PCI	ISA	PCI/ISA
PCE-3B03-00A1E	PICMG1.3	1 (PCIe-16X) 1 (PCIe-4X)	-	-	-
PCE-3B06-00A1E	PICMG1.3	1 (PCIe-16X) 4 (PCIe-1X)	-	-	-
PCE-3B06-03A1E	PICMG1.3	1 (PCIe-16X) 1 (PCIe-1X)	3	-	-
PCA-6105P5-0B2E	PICMG1.0	-	5	-	-
PCA-6106-0B2E	PICMG1.0	-	-	6	-

Optional Accessories

Ordering P/N	Descriptions
1750003780	9 cm 53 CFM Fan
IDT-3120E	Bracket to transfer 3.5" bay to two 2.5" SATA HDD tray